



SHH3P675T08H0 采用沟槽栅极/场截止结构 IGBT 和温度检测 NTC

SHH3P675T08H0 with Trench Gate/Field Stop IGBT and NTC



$V_{CES}=750V$

$I_{C\ nom}=675A$

典型应用

- 交流马达控制
- 逆变器
- 电机传动
- 太阳能发电

Typical Application

- AC Motor Control
- Inverters
- Motor Drives
- Solar Power

电气特性

- 低导通和开关损耗
- 高短路能力
- 反并联超快速软恢复二极管

Electrical Characteristics

- Ultra Low Conduction and Switching Loss
- High Short Circuit Capability
- Including Ultra Fast & Soft Recovery Anti-parallel FWD

机械特性

- 铝碳化硅基板
- 标准封装

Mechanical Properties

- AlSiC Substrate
- Standard Package

| | | | |
|-------------------|----------------------------------|----------------------------|--------------|
| Module Label Code | | | |
| Barcode Code 128: | | Content of the Code | Digit |
| | AP008YYWWPPXX | Sample or Mass Production | 1 |
| | | Module Serial Number | 2 - 5 |
| | | Datecode (Production Year) | 6 - 7 |
| | | Datecode (Production Week) | 8 - 9 |
| | | Production Batch Number | 10 - 11 |
| | | Production Serial Number | 12 - 13 |
| Data Matrix Code: | | | |
| Prepared by : DHY | Date of publication : 2020-08-21 | | |
| Approved by : FJY | Revision : V1.0 | | |

LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.

使用条件和条款

使用条件和条款产品规格书中的数据是专门为技术人员提供的，您和您的技术部门应该针对您的应用来评估产品及产品的所有参数是否适合。

产品规格书中所描述的产品特性是被保证的，任何这种保证严格依照供货协议中所涉及的条件和条款。除此之外，产品和产品的特性没有任何的保证，请注意安装及应用指南中的信息。

如果您有超出规格书所提供的产品信息的要求或者对我们的产品针对的特殊应用有疑虑的话，请联系我们负责您的销售部门（详情查询 www.semiharv.com.cn ）。对那些特别感兴趣的问题我们将提供相应的应用手册，由于技术需要，我们的产品可能含有危险物质。如果需要查询类似问题请联系我们负责您的销售部门。如果您想将我们的产品用于军工、航天、健康、危及生命或者生命维持等应用，请申明。

请注意，对这类应用我们强烈建议

- 执行联合的风险和质量评估；
- 得到质量协议的结论；
- 建立联合的测试和出厂产品检查，我们可以根据测试的实际情况供货；

如果有必要，请根据实际需要将类似的说明给您的客户。

保留产品规格书的修改权。

Terms and conditions of use

Terms of Use The data in the product specifications is provided exclusively for the technician. You and your technical department should evaluate the suitability of the product and all parameters of the product for your application.

The product characteristics described in the product specifications are warranted and any such warranties are strictly in accordance with the terms and conditions of the supply agreement. In addition, there are no guarantees for the characteristics of the products and products. Please pay attention to the information in the installation and application guide.

If you have any questions beyond the product information provided in the specification or have concerns about the specific application for which our products are directed, please contact us in charge of your sales department (for more information, please visit www.semiharv.com.cn). For those issues of particular interest we will provide the corresponding application manuals, which may contain hazardous substances due to technical needs. If you need to find similar questions, please contact us for your sales department. If you want to use our products for military project, aerospace, health, life-threatening or life-sustaining applications, please state.

Please note that we strongly recommend this type of application.

- Perform joint risk and quality assessment;
- conclusion of quality agreement;
- Establish joint test and factory product inspection, we can supply according to the actual situation of the test;

If necessary, please give similar instructions to your customers according to actual needs.

Retain the right to modify product specifications.

LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.

IGBT, 逆变器/ IGBT, Inverter

最大额定值/ Maximum rated Values

| 参数/ Parameter | 符号/ Symbol | 条件/ Conditions | 值/ Values | 单位/ Unit |
|---|--------------------|---|-----------|----------|
| 集电极-发射极电压/ Collector-emitter voltage | V_{CES} | $T_{vj} = 25^{\circ}\text{C}$ | 750 | V |
| 连续集电极直流电流/ Continuous DC collector current | $I_{C\text{ nom}}$ | $T_F = 50^{\circ}\text{C}, T_{vj\text{ max}} = 175^{\circ}\text{C}$ | 675 | A |
| 集电极重复峰值电流/ Repetitive peak collector current | I_{CRM} | $t_p = 1\text{ ms}$ | 1350 | A |
| 总功率损耗/ Total power dissipation | P_{tot} | $T_F = 25^{\circ}\text{C}, T_{vj\text{ max}} = 175^{\circ}\text{C}$ | 1200 | W |
| 栅极-发射极峰值电压/ Gate-emitter peak voltage | V_{GES} | | ± 20 | V |

特征值/ Characteristic Values

| 参数/ Parameter | 符号/ Symbol | 条件/ Conditions | 值/ Values | | | 单位/ Unit | | |
|--|--------------------|---|---|--|-------------|---------------|-------|--------------------|
| | | | 最小/ Min. | 典型/ Typ. | 最大/ Max. | | | |
| 集电极-发射极饱和电压/ Collector-emitter saturation voltage | $V_{CE(SAT)}$ | $V_{GE} = 15\text{ V},$ $I_C = 675\text{ A}$ | $T_{vj} = 25^{\circ}\text{C}$ - $T_{vj} = 125^{\circ}\text{C}$ - $T_{vj} = 150^{\circ}\text{C}$ | 0.8 - - 1.36 1.46 1.49 | 2 - - | V | | |
| 栅极阈值电压/ Gate threshold voltage | $V_{GE(th)}$ | $I_C = 13\text{ mA}, V_{CE} = V_{GE},$ $T_{vj} = 25^{\circ}\text{C}$ | 4.0 | 5.9 | 7.0 | V | | |
| 集电极-发射极截止电流/ Collector-emitter cut-off current | I_{CES} | $V_{CE} = 750\text{ V}, V_{GE} = 0\text{ V}$ $T_{vj} = 25^{\circ}\text{C}$ | - | - | 0.2 | mA | | |
| 栅极-发射极漏电流/ Gate-emitter leakage current | I_{GES} | $V_{CE} = 0\text{ V}, V_{GE} = 20\text{ V},$ $T_{vj} = 25^{\circ}\text{C}$ | - | - | 200 | nA | | |
| 栅极电荷/ Gate charge | Q_G | $V_{CC} = 400\text{ V}, I_C = 450\text{ A},$ $V_{GE} = \pm 15\text{ V}, T_{vj} = 25^{\circ}\text{C}$ | - | 5800 | - | nC | | |
| 开通延迟时间 (电感负载) / Turn-on delay time | $t_{d(on)}$ | $V_{CE} = 400\text{ V},$ $I_C = 450\text{ A},$ $V_{GE} = +15/-8\text{ V},$ $R_{GON} = 10\ \Omega,$ $R_{GOFF} = 10\ \Omega,$ $L_s = 200\ \mu\text{H}$ | $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ | - - - 1.77 1.73 1.71 | - - - | μs | | |
| 上升时间 (电感负载) / Rise time, inductive load | t_r | | $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ | - - - 0.211 0.223 0.228 | - - - | | | |
| 关断延迟时间 (电感负载) / Turn-off delay time, inductive load | $t_{d(off)}$ | | $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ | - - - 2.02 2.09 2.12 | - - - | | | |
| 下降时间 (电感负载) / Fall time, inductive load | t_f | | $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ | - - - 0.588 0.595 0.576 | - - - | | | |
| 开通损耗能量 (每脉冲) / Turn-on energy loss per pulse | E_{on} | | $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ | - - - 16 20 22 | - - - | | mJ | |
| 关断损耗能量 (每脉冲) / Turn-off energy loss per pulse | E_{off} | | $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ | - - - 108 106 102 | - - - | | | |
| 短路数据/ SC data | I_{SC} | | $V_{GE} = 15\text{ V}, V_{CC} = 400\text{ V}$ $t_p = 4\ \mu\text{s}, T_{vj} = 150^{\circ}\text{C}$ | - | 3500 | | | - |
| 结-冷却液热阻/ Thermal resistance, junction-cooling fluid | R_{thJF} | | 每个 IGBT/ per IGBT | - | - | | 0.125 | K/W |
| 在开关状态下的温度/ Temperature under switching conditions | $T_{vj\text{ op}}$ | | | -40 | - | | 150 | $^{\circ}\text{C}$ |

LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.

二极管, 逆变器/ Diode, Inverter

最大额定值/ Maximum ratings Values

| 参数/ Parameter | 符号/ Symbol | 条件/ Conditions | 值/ Values | 单位/ Unit |
|--|------------|-------------------------------|-----------|----------|
| 反复重复峰值电压/ Repetitive peak reverse voltage | V_{RRM} | $T_{vj} = 25^{\circ}\text{C}$ | 750 | V |
| 连续正向电流/ Continuous DC forward current | I_F | | 675 | A |
| 正向重复峰值电流/ Repetitive peak forward current | I_{FRM} | $t_p = 1 \text{ ms}$ | 1350 | A |

特征值/ Characteristic Values

| 参数/ Parameter | 符号/ Symbol | 条件/ Conditions | 值/ Values | | | 单位/ Unit | |
|--|-------------|---|--------------------------------|----------|----------|--------------------|---------------|
| | | | 最小/ Min. | 典型/ Typ. | 最大/ Max. | | |
| 正向电压/ Forward voltage | V_F | $V_{GE} = 0 \text{ V},$ $I_F = 675 \text{ A}$ | $T_{vj} = 25^{\circ}\text{C}$ | 0.8 | 1.88 | 2.0 | V |
| | | | $T_{vj} = 125^{\circ}\text{C}$ | - | 1.91 | - | |
| | | | $T_{vj} = 150^{\circ}\text{C}$ | - | 1.89 | - | |
| 反向恢复峰值电流/ Peak reverse recovery current | I_{RM} | $V_R = 400 \text{ V},$ $I_F = 450 \text{ A}$ | $T_{vj} = 25^{\circ}\text{C}$ | - | 134 | - | A |
| | | | $T_{vj} = 125^{\circ}\text{C}$ | - | 166 | - | |
| | | | $T_{vj} = 150^{\circ}\text{C}$ | - | 182 | - | |
| 恢复电荷/ Recovery charge | Q_r | | $T_{vj} = 25^{\circ}\text{C}$ | - | 8.71 | - | μC |
| | | | $T_{vj} = 125^{\circ}\text{C}$ | - | 9.23 | - | |
| | | | $T_{vj} = 150^{\circ}\text{C}$ | - | 9.21 | - | |
| 反向恢复损耗 (每脉冲) / Reverse recovery energy per pulse | E_{rec} | $I_F = 450 \text{ A},$ $V_R = 400 \text{ V},$ $V_{GE} = -8 \text{ V}$ | $T_{vj} = 25^{\circ}\text{C}$ | - | 3.2 | - | mJ |
| | | | $T_{vj} = 125^{\circ}\text{C}$ | - | 5.3 | - | |
| | | | $T_{vj} = 150^{\circ}\text{C}$ | - | 6.5 | - | |
| 结-冷却液热阻/ Thermal resistance, junction-cooling fluid | R_{thJF} | 每个二极管/ per diode | - | - | 0.162 | K/W | |
| 在开关状态下的温度/ Temperature under switching conditions | $T_{vj op}$ | | -40 | - | 150 | $^{\circ}\text{C}$ | |

负温度系数热敏电阻/ NTC-Thermistor

特征值/ Characteristic Values

| 参数/ Parameter | 符号/ Symbol | 条件/ Conditions | 值/ Value | 单位/ Unit |
|-------------------------------|----------------|---|----------|------------|
| 额定电阻值/ Rated resistance | R_{25} | $T_{NTC} = 25^{\circ}\text{C}$ | 5.00 | k Ω |
| R100 偏差/ Deviation of R100 | $ \Delta R /R$ | $T_{NTC} = 100^{\circ}\text{C}, R_{100} = 493 \Omega$ | 5 | % |
| B-值/ B-value | $B_{25/50}$ | 25 和 50 $^{\circ}\text{C}$ 电阻值计算得到/ Calculated from resistance value at 25 $^{\circ}\text{C}$ and 50 $^{\circ}\text{C}$ | 3375 | K |
| B-值/ B-value | $B_{25/80}$ | 25 和 80 $^{\circ}\text{C}$ 电阻值计算得到/ Calculated from resistance value at 25 $^{\circ}\text{C}$ and 80 $^{\circ}\text{C}$ | 3411 | K |
| B-值/ B-value | $B_{25/100}$ | 25 和 100 $^{\circ}\text{C}$ 电阻值计算得到/ Calculated from resistance value at 25 $^{\circ}\text{C}$ and 100 $^{\circ}\text{C}$ | 3433 | K |

LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.

模块/ Module

| 参数/ Parameter | 符号/ Symbol | 条件/ Conditions | 值/ Values | 单位/ Unit |
|--|-------------------|--------------------------------|--------------------------------|----------|
| 绝缘测试电压/ Isolation test voltage | V _{ISOL} | RMS, f = 0 Hz, t = 1.2 sec | 4.7 | kV |
| 模块基板材料/ Material of Module baseplate | | | AlSiC | |
| 内部绝缘材料/ Material of Internal Isolation | | | Al ₂ O ₃ | |
| 爬电距离/ Creepage distance | | 端子-散热片/ Terminal to heatsink | 7.0 | mm |
| | | 端子- 端子 / terminal to terminal | 5.5 | |
| 电气间隙/Clearance | | 端子- 散热片 / terminal to heatsink | 7.0 | mm |
| | | 端子- 端子 / terminal to terminal | 5.0 | |
| 模块杂散电感/ Stray inductance module | L _S | | 53 | nH |
| 存储温度/ Storage temperature | T _{stg} | | -40 ~ 125 | °C |
| 模块安装扭矩/ Mounting torque for module mounting | M | 螺丝 M6/ Screw M6 | 3.0 ~ 6.0 | N·m |
| 端子联接扭矩/ Terminal connection torque | M | 螺丝 M6/ Screw M6 | 3.0 ~ 6.0 | N·m |
| 重量/ Weight | G | | 630 | g |


LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.

输出特性 IGBT, 逆变器 (典型)

Output characteristic IGBT, Inverter (typical)


$I_C = f(V_{CE})$
 $V_{GE} = 15\text{ V}$



输出特性 IGBT, 逆变器 (典型)

Output characteristic IGBT, Inverter (typical)


$I_C = f(V_{CE})$
 $T_{vj} = 150^\circ\text{C}$



传输特性 IGBT, 逆变器 (典型)

Transfer characteristic IGBT, Inverter (typical)


$I_C = f(V_{GE})$
 $V_{CE} = 20\text{ V}$



开关损耗 IGBT, 逆变器 (典型)

Switching losses IGBT, Inverter (typical)


$E_{on} = f(I_C), E_{off} = f(I_C)$
 $V_{GE} = \pm 15\text{ V}, R_{Gon} = 10\ \Omega, R_{Goff} = 10\ \Omega, V_{CE} = 400\text{ V}$




LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.


瞬态热阻抗 IGBT, 逆变器 (典型)
 Transient thermal impedance IGBT, Inverter (typical)
 $Z_{thJC} = f(t)$




正向偏压特性 二极管, 逆变器 (典型)
 Forward characteristic of Diode, Inverter (typical)
 $I_F = f(V_F)$



瞬态热阻抗 二极管, 逆变器 (典型)
 Transient thermal impedance Diode, Inverter (typical)
 $Z_{thJC} = f(t)$




开关损耗 二极管, 逆变器 (典型)
 Switching losses Diode, Inverter (typical)
 $E_{rec} = f(I_F), R_{Gon} = 10 \Omega, V_{CE} = 400 V$




LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.

接线图 / Circuit_diagram_headline



封装尺寸 / Package outlines



单位: mm

LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.

版本履历 / Revision History

| Page or Reference | Description of change |
|-------------------|-----------------------|
| V1.0 | Initial Datasheet. |
| | |
| | |

LEGAL NOTICE

This document is to be treated confidentially. It may only be made accessible to authorized persons. It may only be made available to third parties with the expressed written consent of Zhejiang Xinfeng Technology Co., Ltd.